



<b>Product name</b>	:	<b>MoTip Hollow Section Wax</b>	
<b>Article number</b>	:	<b>000046</b>	
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b>	
		<b>Wolframweg 2</b>	
		<b>NL-8471 XC WOLVEGA</b>	
		<b>Telephone number</b>	<b>+31 561 – 69 44 00</b>
		<b>Telefax number</b>	<b>+31 561 – 69 44 31</b>

---

### Product description

High quality preservative to treat the hollow spaces in vehicle bodywork.

### Product characteristics

Excellent corrosion prevention  
Excellent adhesion  
Resistant to weather influences  
Resistant to weak acids and bases  
Good penetrating quality

### Physical and Chemical Characteristics

Contents	:	500 ml
Colour	:	White transparent
VOC-content	:	Approximately 77% w/w

### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

### Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes.

Apply the wax generously in the hollow areas by means of the adapter.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).