



Dry Charge Lead Battery Safety Data Sheet

according to Regulation (EU) 2015/830

Document:	SDS 09
Issue No:	1
Issue Date:	19-03-2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Product name : High Performance MF, VRLA MF, YuMicron & Conventional Series - Dry Charged Lead Battery

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the article : Motorcycle & power sport electric storage/starter battery

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier: GS Yuasa Battery Europe Ltd
Address: Unit 22, Rassau Industrial Estate,
Ebbw Vale, NP23 5SD
United Kingdom

National Contacts
France: GS Yuasa Battery France S.A.
Contact: Christian RAYNAUD (Technical Manager)
Tel: (+33) 0474-95-90-95
e-mail: christian.raynaud@gs-yuasa.fr
Language: French & English

Germany: GS Yuasa Battery Germany GmbH
Contact: Joachim HEER (UPS / Project Manager)
Tel: (+49) 0211-41790-15
e-mail: Joachim.Heer@gs-yuasa.de
Language: German & English

Iberia: GS Yuasa Battery Iberia S.A.
Contact: Antonio PULIDO MARTINEZ (Director Commercial Industrial)
Tel: (+34) 091-748-89-19
e-mail: antonio.pulido@gs-yuasa.es
Language: Spanish & English

Italy: GS Yuasa Battery Italy Srl.
Contact: Marco FILIPPI (Technical Manager)
Tel: (+39) 02-3800-91-08
e-mail: marco.filippi@gs-yuasa.it
Language: Italian & English

UK: GS Yuasa Battery Sales UK Ltd.
Contact: Matt JORDAN (General Manager)
Tel: (+44) 01793-833-562
e-mail: Matt.Jordan@gs-yuasa.uk
Language: English language only

1.4. Emergency telephone number

Emergency number : +44(0)1793833562 (09:00– 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture/Substance: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Reproductive toxicity, Category 1A H360Fd
Specific target organ toxicity (repeated exposure) Category 1 H372
Hazardous to the aquatic environment — Acute Hazard, Category 1 H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1 H410

Full text of H statements : see section 16

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

GHS09

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H360Fd - May damage fertility. Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P264 - Wash ... thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P273 - Avoid release to the environment

2.3. Other hazards

other hazards which do not result in classification :

Lead may be toxic to blood, kidneys, central nervous system.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Antimony	(CAS No) 7440-36-0 (EC no) 231-146-5 (REACH-no) not available	0,2	Not classified
Lead	(CAS No) 7439-92-1 (EC no) 231-100-4 (REACH-no) not available	89 - 92	Repr. 1A, H360 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately.
First-aid measures after skin contact	: Rinse immediately with plenty of water for 15 minutes. Remove contaminated clothing, including shoes, after flushing has begun. If a battery ruptures, do not rub or scratch exposed skin.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If battery ruptures, do not rub or scratch exposed eye.
First-aid measures after ingestion	: If solution of a battery chemicals have been swallowed and the person is conscious, give one glass of water. Do NOT induce vomiting. Vomiting may occur spontaneously. Never give anything by mouth to an unconscious person. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: In case of repeated or prolonged exposure : May cause respiratory irritation.
Symptoms/injuries after skin contact	: Direct contact with internal components of a battery can be severely irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition. Skin contact may aggravate dermatitis.
Symptoms/injuries after eye contact	: Dust from this product may cause eyes irritation.
Symptoms/injuries after ingestion	: Ingestion may cause nausea and vomiting. Abdominal pain. Diarrhea.

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : On burning formation of metallic fumes. Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

Hazardous decomposition products in case of fire : Toxic gases and fumes may be released in a fire.

5.3. Advice for firefighters

Protective equipment for firefighters : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.

Emergency procedures : Evacuate area.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.

Emergency procedures : Evacuate unnecessary personnel.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Wet clean or vacuum up solids.

Methods for cleaning up : Use clean-up methods that avoid dust generation (vacuum wet). Collect all waste in suitable and labelled containers and dispose according to local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Protect from physical damage.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Since emptied containers retain product residue, follow label warnings even after container is emptied. Proper grounding procedures to avoid static electricity should be followed. Non-static creating clothing and conductive shoes should be worn.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.

Storage conditions : Store in a dry, cool and well-ventilated place. Keep away from heat and direct sunlight. Protect containers against damage.

Incompatible products : Strong bases. Strong acids.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

Lead (7439-92-1)		
EU	European BEI	(Medium: blood - Time: no restriction - Parameter: Lead (binding biological limit value) 0,075 mg/m ³ (Medium: air - Time: 40 hours per week - Parameter: Lead (TWA medical surveillance threshold in air measured as a time weighted average over 40 hours per week) (Medium: blood - Time: no restriction - Parameter: Lead (medical surveillance threshold measured in individual workers)
Austria	MAK (mg/m ³)	0,1 mg/m ³ (inhalable fraction)
Austria	MAK Short time value (mg/m ³)	0,4 mg/m ³ (inhalable fraction)
Bulgaria	OEL TWA (mg/m ³)	0,05 mg/m ³
Bulgaria	Bulgaria - BEI	300 µg/l (Medium: blood - Time: not fixed - Parameter: Lead (for women under 45 years old) 400 µg/l (Medium: blood - Time: not fixed - Parameter: Lead)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	0,15 mg/m ³
Croatia	Croatia - BEI	(Medium: blood - Time: not critical - Parameter: Lead (Medical surveillance should be carried out when the limit value of Lead in blood of workers >40 µg/100mL blood) (Medium: urine - Time: single sample or urine collected over 24 hours - Parameter: Lead (For all results that are expressed on Creatinine, Creatinine concentration <0.5 g/L and >3.0 g/L should not be considered) (Medium: blood - Time: not critical - Parameter: .delta.- Aminolevulinic acid dehydratase) (Medium: blood - Time: after exposure during 2-3 months (light protected sample) - Parameter: Protoporphyrin in erythrocytes (Interference of Iron deficiency (anemia sideropenic))
Cyprus	OEL TWA (mg/m ³)	0,15 mg/m ³
Czech Republic	Expoziční limity (PEL) (mg/m ³)	0,05 mg/m ³
Czech Republic	Czech Republic - BEI	(Medium: urine - Time: discretionary - Parameter: 5- Aminolevulinic acid (For short term continual exposures <=30 calendar days) (Medium: urine - Time: discretionary - Parameter: Coproporphyrin (For short term continual exposures <=30 calendar days) (Medium: urine - Time: discretionary - Parameter: 5- Aminolevulinic acid (For short term continual exposures <=30 calendar days) (Medium: urine - Time: discretionary - Parameter: Coproporphyrin (For short term continual exposures <=30 calendar days) 0,4 mg/l (Medium: blood - Time: discretionary - Parameter: Lead)
Denmark	Grænseværdie (langvarig) (mg/m ³)	0,05 mg/m ³ (dust, fume and powder)
Denmark	Denmark - BEI	(Medium: blood - Parameter: Lead)
Estonia	OEL TWA (mg/m ³)	0,1 mg/m ³ (total dust) 0,05 mg/m ³ (respirable dust)
Finland	HTP-arvo (8h) (mg/m ³)	0,1 mg/m ³ (all works)
Finland	Finland - BEI	(Medium: blood - Time: not critical - Parameter: Lead)
France	VME (mg/m ³)	0,1 mg/m ³ (restrictive limit)
France	France - BEI	400 µg/l (Medium: blood - Parameter: Lead (biological limit value, men) 300 µg/l (Medium: blood - Parameter: Lead (biological limit value, women) 200 µg/l (Medium: blood - Parameter: Lead (medical surveillance value, men) 100 µg/l (Medium: blood - Parameter: Lead (medical surveillance value, women)
Germany	TRGS 903 (BGW)	300 µg/l (Medium: whole blood - Time: no restriction - Parameter: Lead (women age below 45 years) 400 µg/l (Medium: whole blood - Time: no restriction - Parameter: Lead (women 45 years and older)
Gibraltar	OEL TWA (mg/m ³)	0,15 mg/m ³

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

Lead (7439-92-1)		
Gibraltar	Gibraltar - BEI	(Medium: blood - Time: no restriction - Parameter: Lead (binding biological limit value) 0,075 mg/m ³ (Medium: air - Time: 40 hours per week - Parameter: Lead (medical surveillance threshold measured in individual employees)) (Medium: blood - Time: no restriction - Parameter: Lead (medical surveillance threshold measured in individual employees))
Greece	OEL TWA (mg/m ³)	0,15 mg/m ³
Hungary	AK-érték	0,15 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	0,15 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	0,45 mg/m ³ (calculated)
Italy	OEL TWA (mg/m ³)	0,075 mg/m ³
Italy	Italy - BEI	(Medium: blood - Time: end of workweek (Lead remediation must be performed when workers of fertile age have Lead in blood levels >40 µg/100mL))
Latvia	OEL TWA (mg/m ³)	0,005 mg/m ³
Latvia	Latvia - BEI	(Medium: blood - Parameter: Lead (reference value in blood for occupationally unexposed population <=10 µg/100 mL) (Medium: urine - Parameter: Coproporphyrin (reference value 22-57µg/g Creatinine) (Medium: urine - Parameter: Aminolevulinic acid (reference value 0.5-2.5mg/g Creatinine))
Lithuania	IPRV (mg/m ³)	0,15 mg/m ³ (inhalable fraction) 0,07 mg/m ³ (respirable fraction)
Luxembourg	OEL TWA (mg/m ³)	0,15 mg/m ³
Luxembourg	Luxembourg - BEI	(Medium: blood - Parameter: Lead) 0,075 mg/m ³ (Medium: blood - Parameter: Lead (medical surveillance threshold in air measured as a time weighted average over 40 hours per week) (Medium: blood - Parameter: Lead (medical surveillance threshold measured in individual workers))
Poland	NDS (mg/m ³)	0,05 mg/m ³
Portugal	OEL TWA (mg/m ³)	0,15 mg/m ³ (mandatory indicative limit value)
Romania	OEL TWA (mg/m ³)	0,05 mg/m ³
Romania	OEL STEL (mg/m ³)	0,10 mg/m ³
Romania	Romania - BEI	150 µg/l (Medium: urine - Time: end of shift - Parameter: Lead) (Medium: blood - Time: end of shift - Parameter: Lead) (Medium: hair - Time: end of shift - Parameter: Lead) 10 mg/l (Medium: urine - Time: end of shift - Parameter: .delta.-Aminolevulinic acid) 300 µg/l (Medium: urine - Time: end of shift - Parameter: Coproporphyrin) (Medium: blood - Time: end of shift - Parameter: Erythrocytes protoporphyrin)
Slovakia	NPHV (priemerná) (mg/m ³)	0,15 mg/m ³
Slovakia	Slovakia - BEI	400 µg/l (Medium: blood - Time: not critical - Parameter: Lead) 100 µg/l (Medium: blood - Time: not critical - Parameter: Lead (women younger than 45 years of age)) 15 mg/l (Medium: urine - Time: not critical - Parameter: .delta.-Aminolevulinic acid) 6 mg/l (Medium: urine - Time: not critical - Parameter: .delta.-Aminolevulinic acid (women younger than 45 years of age)) 0,30 mg/l (Medium: urine - Time: not critical - Parameter: Coproporphyrins)
Slovenia	OEL TWA (mg/m ³)	0,1 mg/m ³ (inhalable fraction)
Slovenia	OEL STEL (mg/m ³)	0,4 mg/m ³ (inhalable fraction)
Spain	VLA-ED (mg/m ³)	0,15 mg/m ³

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

Lead (7439-92-1)		
Spain		(Medium: blood - Time: not critical - Parameter: Lead (3,K))
Sweden	nivågränsvärde (NVG) (mg/m ³)	0,1 mg/m ³ (total inhalable dust) 0,05 mg/m ³ (total respirable dust)
United Kingdom	WEL TWA (mg/m ³)	0,15 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	0,45 mg/m ³ (calculated)
Norway	Grenseverdier (AN) (mg/m ³)	0,05 mg/m ³ (dust and fume)
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	0,05 mg/m ³ (dust and fume)
Switzerland	VME (mg/m ³)	0,1 mg/m ³ (inhalable dust)
Switzerland	VLE (mg/m ³)	0,8 mg/m ³ (inhalable dust)
Switzerland	Switzerland - BEI	400 µg/l (Medium: whole blood - Time: no restrictions - Parameter: Lead (men and women over 45 years old, X)) 100 µg/l (Medium: whole blood - Time: no restrictions - Parameter: Lead (women less than 45 years old, X))
Australia	TWA (mg/m ³)	0,15 mg/m ³ (dust and fume)
Canada (Quebec)	VEMP (mg/m ³)	0,05 mg/m ³
USA - ACGIH	ACGIH TWA (mg/m ³)	0,05 mg/m ³
USA - IDLH	US IDLH (mg/m ³)	100 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	0,050 mg/m ³
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
Antimony (7440-36-0)		
Austria	MAK (mg/m ³)	0,5 mg/m ³ (inhalable fraction)
Austria	MAK Short time value (mg/m ³)	5 mg/m ³ (inhalable fraction)
Belgium	Limit value (mg/m ³)	0,5 mg/m ³
Bulgaria	OEL TWA (mg/m ³)	0,5 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	0,5 mg/m ³
Czech Republic	Expoziční limity (PEL) (mg/m ³)	0,5 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	0,5 mg/m ³ (powder)
Estonia	OEL TWA (mg/m ³)	0,5 mg/m ³
Finland	HTP-arvo (8h) (mg/m ³)	0,5 mg/m ³
France	VME (mg/m ³)	0,5 mg/m ³
Greece	OEL TWA (mg/m ³)	0,5 mg/m ³
Hungary	AK-érték	0,5 mg/m ³
Hungary	CK-érték	2 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	0,5 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	1,5 mg/m ³ (calculated)
Latvia	OEL TWA (mg/m ³)	0,2 mg/m ³ (metallic dust)
Lithuania	IPRV (mg/m ³)	0,5 mg/m ³
Netherlands	Grenswaarde TGG 8H (mg/m ³)	0,5 mg/m ³
Poland	NDS (mg/m ³)	0,5 mg/m ³
Portugal	OEL TWA (mg/m ³)	0,5 mg/m ³
Romania	OEL TWA (mg/m ³)	0,20 mg/m ³
Romania	OEL STEL (mg/m ³)	0,50 mg/m ³
Romania	Romania - BEI	1 mg/l (Medium: urine - Time: end of shift - Parameter: Antimony)
Slovakia	NPHV (priemerná) (mg/m ³)	0,5 mg/m ³ (total dust)
Slovenia	OEL TWA (mg/m ³)	0,5 mg/m ³ (inhalable fraction)
Slovenia	OEL STEL (mg/m ³)	2 mg/m ³ (inhalable fraction)
Spain	VLA-ED (mg/m ³)	0,5 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	0,25 mg/m ³ (total inhalable dust)
United Kingdom	WEL TWA (mg/m ³)	0,5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	1,5 mg/m ³ (calculated)
Norway	Grenseverdier (AN) (mg/m ³)	0,5 mg/m ³

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

Antimony (7440-36-0)

Norway	Grønseverdier (Korttidsverdi) (mg/m ³)	0,5 mg/m ³
Switzerland	VME (mg/m ³)	0,5 mg/m ³ (inhalable dust)
Australia	TWA (mg/m ³)	0,5 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	0,5 mg/m ³
USA - ACGIH	ACGIH TWA (mg/m ³)	0,5 mg/m ³
USA - IDLH	US IDLH (mg/m ³)	50 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	0,5 mg/m ³
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	0,5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Mechanical ventilation is recommended. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Personal protective equipment	: Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.
Hand protection	: Wear suitable gloves tested to EN374.
Eye protection	: Chemical goggles or face shield with safety glasses. DIN EN 166
Skin and body protection	: Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of soap and water.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140 with Type A/P2 filter or better.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Bluish grey metal.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 252,2222 - 360 °C
Freezing point	: No data available
Boiling point	: 1380 °C
Flash point	: Non-flammable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 9,6 - 11,3 g/m ³
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable at normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Overcharging. Remove all sources of ignition. If battery ruptures, avoid contact with organic materials and alkaline materials. Mechanical impact.

10.5. Incompatible materials

If battery ruptures, avoid contact with organic materials and alkaline materials. If battery ruptures, avoid contact with organic materials and alkaline materials.

10.6. Hazardous decomposition products

Toxic fumes may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Antimony (7440-36-0)

LD50 oral rat	7 g/kg
---------------	--------

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility. Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Lead (7439-92-1)

LC50 fish 1	0,44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
-------------	--

LC50 fish 2	1,17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
-------------	---

EC50 Daphnia 1	600 µg/l (Exposure time: 48 h - Species: water flea)
----------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Dry Charge Lead Battery

Ecology - soil	persistent.
----------------	-------------

12.5. Results of PBT and vPvB assessment

Dry Charge Lead Battery

Results of PBT assessment	The PBT and vPvB criteria of Annex XIII to the Regulation does not apply to inorganic substances
---------------------------	--

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose of contents/container to comply with applicable local, national and international regulations.
Waste treatment methods	: Recycling the product is recommended. Waste must be disposed of in accordance with federal, state, and local environmental control regulations.
Waste disposal recommendations	: Consult the appropriate local waste disposal expert about waste disposal. . Since emptied containers retain product residue, follow label warnings even after container is emptied.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : Lead is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Lead is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Lead is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Indication of changes:

According to Regulation (EU) 2015/830 (REACH Annex II).

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Repr. 1A	Reproductive toxicity, Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H360	May damage fertility or the unborn child
H360Fd	May damage fertility. Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Dry Charge Lead Battery

Safety Data Sheet

according to Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product