
Product name	:	MoTip Gasket Remover
Article number	:	090403
Supplier / Producer	:	MOTIP DUPLI B.V. Wolfraamweg 2 NL-8471 XC WOLVEGA Telephone number +31 561 – 69 44 00 Telefax number +31 561 – 69 44 31

Product description

High quality spray to fast and easily remove dried adhesives and seals, as well as hardened sealing material from car and machine parts.

Applications

Cylinder Heads
Gear Boxes
Exhausts
Crankcases
Sanitary Fittings
Water and oil pumps
Electro engines

Product characteristics

User-friendly
High dissolving properties
Optimum effect in view of high viscosity
Non-conductive
Slight gel structure
Non-corrosive
Directed jetspray
360° valve



Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Dimethoxymethaan
VOC-content	:	Approximately 95% w/w
Colour	:	Transparent
Scent	:	Ether
Relative density at 20°C	:	0,75 g/ml
Yield	:	1,0 – 1,5 g/sec
Vapour pressure at 20°C	:	2 to 3 bar
pH-value	:	Neutral

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Cover lacquered and plastic parts.

Apply in an equal layer on the parts to be treated and allow to take effect for approximately 10 minutes.
Carefully remove the dissolved residues with a filling-knife. With persistent contamination, repeat the treatment.